

---

**pyrcmip**

***Release 0.2.1+0.gce02ce1.dirty***

**Zeb Nicholls, Jared Lewis**

**Sep 01, 2020**



# DOCUMENTATION

|          |                                   |           |
|----------|-----------------------------------|-----------|
| <b>1</b> | <b>License</b>                    | <b>3</b>  |
| <b>2</b> | <b>References</b>                 | <b>5</b>  |
| 2.1      | Installation . . . . .            | 5         |
| 2.2      | Submitting results . . . . .      | 5         |
| 2.3      | Development . . . . .             | 7         |
| 2.4      | Command-line interface . . . . .  | 12        |
| 2.5      | Database API . . . . .            | 13        |
| 2.6      | Errors API . . . . .              | 15        |
| 2.7      | IO API . . . . .                  | 15        |
| 2.8      | Metric Calculations API . . . . . | 16        |
| 2.9      | Plotting API . . . . .            | 17        |
| 2.10     | Stats API . . . . .               | 17        |
| 2.11     | Validate API . . . . .            | 17        |
| 2.12     | Changelog . . . . .               | 19        |
| <b>3</b> | <b>Index</b>                      | <b>23</b> |
|          | <b>Bibliography</b>               | <b>25</b> |
|          | <b>Python Module Index</b>        | <b>27</b> |
|          | <b>Index</b>                      | <b>29</b> |



pyrcmip is a tool for validating and uploading results to [RCMIP](#). The Reduced Complexity Model Intercomparison Project (RCMIP) is a project to evaluate reduced-complexity (also known as simple) climate models and compare them against CMIP coupled models.



## LICENSE

pyrcmip is free software under a BSD 3-Clause License, see [LICENSE](#).

If you make use of pyrcmip or any of the RCMIP project, please cite Nicholls et al., *GMDD* 2020 [1].





## REFERENCES

### 2.1 Installation

The easiest way to install pyrcmip is with [pip](#). At this stage pyrcmip only supports Python 3.6+.

```
# if you're using a virtual environment, make sure you're in it
pip install pyrcmip
```

### 2.2 Submitting results

If you're interested in submitting results to RCMIP then you're in the right place. Here we go through the process of preparing and submitting results to RCMIP. If you have any issues with this guide, or feel it could be improved, please don't hesitate to raise an issue in the [pyrcmip issue tracker](#) or [make a merge request](#).

A set of Jupyter Notebooks for the running the RCMIP experiments and uploading the results using the [Geoffroy et al. \(2013\)](#) two-layer model, as implemented in [openscm-twolayermodel](#) are available in [notebooks/example-model-pipeline](#). These notebooks can be launched directly using [binder](#). We would love to share more examples of running your models using the RCMIP protocol.

- *Performing the experiments*
- *Preparing the submission*
  - *Timeseries*
    - \* *Differences from RCMIP Phase 1*
  - *Model reported metrics*
  - *Metadata*
    - \* *Differences from RCMIP Phase 1*
- *Validating the submission*
- *Uploading the submission*

## 2.2.1 Performing the experiments

The first step to submitting is performing the experiments. Our protocol is currently available from the [RCMIP website](#), under the [initial datasets header](#). Please follow the protocol as closely as possible. If you have any questions about the protocol or how to follow it, please raise an issue in the [pyrcmip issue tracker](#).

## 2.2.2 Preparing the submission

Having performed the experiments, next you need to prepare your submission. Submission via pyrcmip is a largely automated process, hence looks a little different to how submission looked in RCMIP phase 1.

For submission via pyrcmip, you need three things:

1. Timeseries to be submitted
2. Model reported metrics
3. Metadata about your submission

### Timeseries

The first part of the submission is the timeseries. These can be provided in one of three ways.

1. As the `your_data` sheet in our [submission protocol](#) (e.g. [https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip\\_model\\_output\\_test.xlsx](https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip_model_output_test.xlsx)).
2. As a standalone csv (or gzipped csv) of the same format as the `your_data` sheet in our [submission protocol](#) ([https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip\\_model\\_output\\_test.csv](https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip_model_output_test.csv)).
3. As a standalone netCDF file in `scmdata`'s netCDF format (e.g. [https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip\\_model\\_output\\_test.csv](https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip_model_output_test.csv), further details on the format at <https://github.com/openscm/scmdata/blob/v0.6.3/notebooks/netcdf.ipynb>).

### Differences from RCMIP Phase 1

For those who submitted to RCMIP Phase 1, please note the following two differences:

1. we now ask for an extra column `ensemble_member`, which provides an index so we can distinguish different model configurations within a probabilistic ensemble
2. the column headings have changed slightly (our readers should be able to handle the old style, but updating if you can would be much appreciated)

### Model reported metrics

We also ask you to report some metrics which cannot be derived from any RCMIP experiments. At this stage, the only such metric is Equilibrium Climate Sensitivity (none of our experiments are long enough to reach true equilibrium). We ask that you submit a csv which documents the Equilibrium Climate Sensitivity of each `ensemble_member` provided in the timeseries part of the submission. An example of such a csv is shown in [https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip\\_model\\_reported\\_metrics\\_test.csv](https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip_model_reported_metrics_test.csv).

## Metadata

The final part of the submission is metadata. This simply provides metadata about your model which can be used as documentation. This metadata can be provided in one of two ways:

1. as a csv of the same format as [https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip\\_model\\_metadata\\_test.csv](https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip_model_metadata_test.csv)
2. by saving the `meta_model` sheet of our [submission protocol](#) as a standalone csv (this should result in a csv like <https://gitlab.com/rcmip/pyrcmip/-/tree/master/tests/data/rcmip-model-meta-test.csv>)

## Differences from RCMIP Phase 1

We have only made one change compared to RCMIP Phase 1:

1. we have removed the ECS column from the `meta_model` sheet

### 2.2.3 Validating the submission

Once you have prepared your submission, you can then use RCMIP's command-line interface to validate it. This is done using the `rcmip validate` command. For full details, please see the [validate](#) section in our *Command-line interface* documentation. This command will validate your submission, highlighting any errors it finds and providing you with a green light otherwise. If your submission does not pass validation, you will not be able to upload it in the next step. If you have any questions or issues with validation, please raise an issue in the [pyrcmip issue tracker](#).

### 2.2.4 Uploading the submission

Once your submission has been validated, you can then upload it. This is done using the `rcmip upload` command. For full details, please see the [upload](#) section in our *Command-line interface* documentation. This command will validate (again, just in case) and then upload your submission (assuming the validation passed). If you have any questions or issues with upload, please raise an issue in the [pyrcmip issue tracker](#).

## 2.3 Development

If you're interested in contributing to pyrcmip, we'd love to have you on board! This section of the docs details how to get setup to contribute and how best to communicate.

- *Contributing*
- *Getting setup*
  - *Getting help*
    - \* *Development tools*
    - \* *Other tools*
- *Formatting*
- *Buiding the docs*
  - *Gotchas*

- *Docstring style*
- *Releasing*
  - *First step*
  - *PyPI*
  - *Push to repository*
  - *Conda*
- *Why is there a Makefile in a pure Python repository?*
- *Why did we choose a BSD 2-Clause License?*

### 2.3.1 Contributing

All contributions are welcome, some possible suggestions include:

- tutorials (or support questions which, once solved, result in a new tutorial :D)
- blog posts
- improving the documentation
- bug reports
- feature requests
- pull requests

Please report issues or discuss feature requests in the [pyrcmpip issue tracker](#). If your issue is a feature request or a bug, please use the templates available, otherwise, simply open a normal issue :)

As a contributor, please follow a couple of conventions:

- Create issues in the [pyrcmpip issue tracker](#) for changes and enhancements, this ensures that everyone in the community has a chance to comment
- Be welcoming to newcomers and encourage diverse new contributors from all backgrounds: see the [Python Community Code of Conduct](#)

### 2.3.2 Getting setup

To get setup as a developer, we recommend the following steps (if any of these tools are unfamiliar, please see the resources we recommend in [Development tools](#)):

1. Install conda and make
2. Run `make conda-environment`, if that fails you can try doing it manually by reading the commands from the Makefile
3. Make sure the tests pass by running `make test`, as above if that fails you can try doing it manually by reading the commands from the Makefile

### Getting help

Whilst developing, unexpected things can go wrong (that's why it's called 'developing', if we knew what we were doing, it would already be 'developed'). Normally, the fastest way to solve an issue is to contact us via the [issue](#)

[tracker](#). The other option is to debug yourself. For this purpose, we provide a list of the tools we use during our development as starting points for your search to find what has gone wrong.

## Development tools

This list of development tools is what we rely on to develop pyrcmip reliably and reproducibly. It gives you a few starting points in case things do go inexplicably wrong and you want to work out why. We include links with each of these tools to starting points that we think are useful, in case you want to learn more.

- [Git](#)
- [Make](#)
- [Conda virtual environments](#)
  - note the common gotcha that `source activate` has now changed to `conda activate`
  - we use conda instead of pure pip environments because they help us deal with Iris’ dependencies: if you want to learn more about pip and pip virtual environments, check out [this introduction](#)
- [Tests](#)
  - we use a blend of [pytest](#) and the inbuilt Python testing capabilities for our tests so checkout what we’ve already done in `tests` to get a feel for how it works
- [Continuous integration \(CI\)](#)
  - we use [GitLab CI](#) for our CI but there are a number of good providers
- [Jupyter Notebooks](#)
  - we’d recommend simply installing `jupyter` (`conda install jupyter`) in your virtual environment
- [Sphinx](#)

## Other tools

We also use some other tools which aren’t necessarily the most familiar. Here we provide a list of these along with useful resources.

- [Regular expressions](#)
  - we use [regex101.com](#) to help us write and check our regular expressions, make sure the language is set to Python to make your life easy!

### 2.3.3 Formatting

To help us focus on what the code does, not how it looks, we use a couple of automatic formatting tools. These automatically format the code for us and tell use where the errors are. To use them, after setting yourself up (see [Getting setup](#)), simply run `make black` and `make flake8`. Note that `make black` can only be run if you have committed all your work i.e. your working directory is ‘clean’. This restriction is made to ensure that you don’t format code without being able to undo it, just in case something goes wrong.

### 2.3.4 Buiding the docs

After setting yourself up (see [Getting setup](#)), building the docs is as simple as running `make docs` (note, run `make -B docs` to force the docs to rebuild and ignore make when it says ‘... index.html is up to date’). This will build the docs for you. You can preview them by opening `docs/build/html/index.html` in a browser.

For documentation we use [Sphinx](#). To get ourselves started with Sphinx, we started with [this example](#) then used [Sphinx’s getting started guide](#).

#### Gotchas

To get Sphinx to generate pdfs (rarely worth the hassle), you require [Latexmk](#). On a Mac this can be installed with `sudo tlmgr install latexmk`. You will most likely also need to install some other packages (if you don’t have the full distribution). You can check which package contains any missing files with `tlmgr search --global --file [filename]`. You can then install the packages with `sudo tlmgr install [package]`.

#### Docstring style

For our docstrings we use numpy style docstrings. For more information on these, [here is the full guide](#) and [the quick reference we also use](#).

### 2.3.5 Releasing

The steps to release a new version of pyrcmpip are shown below. Please do all the steps below and all the steps for both release platforms.

#### First step

1. Test installation with dependencies `make test-install`
2. Update `CHANGELOG.rst`:
  - add a header for the new version between `master` and the latest bullet point
  - this should leave the section underneath the master header empty
3. `git add .`
4. `git commit -m "Prepare for release of vX.Y.Z"`
5. `git tag vX.Y.Z`
6. Test version updated as intended with `make test-install`

#### PyPI

If uploading to PyPI, do the following (otherwise skip these steps)

1. `make publish-on-testpypi`
2. Go to [test PyPI](#) and check that the new release is as intended. If it isn’t, stop and debug.
3. Test the install with `make test-testpypi-install` (this doesn’t test all the imports as most required packages are not on test PyPI).

Assuming test PyPI worked, now upload to the main repository

1. `make publish-on-pypi`
2. Go to [pyrcmip's PyPI](#) and check that the new release is as intended.
3. Test the install with `make test-pypi-install` (a pip only install will throw warnings about Iris not being installed, that's fine).

## Push to repository

Finally, push the tags and the repository

1. `git push`
2. `git push --tags`

## Conda

*Note:* Conda releases are not yet operational

1. If you haven't already, fork the [pyrcmip conda feedstock](#). In your fork, add the feedstock upstream with `git remote add upstream https://github.com/conda-forge/pyrcmip-feedstock` (upstream should now appear in the output of `git remote -v`)
2. Update your fork's master to the upstream master with:
  1. `git checkout master`
  2. `git fetch upstream`
  3. `git reset --hard upstream/master`
3. Create a new branch in the feedstock for the version you want to bump to.
4. Edit `recipe/meta.yaml` and update:
  - version number in line 1 (don't include the 'v' in the version tag)
  - the build number to zero (you should only be here if releasing a new version)
  - update `sha256` in line 9 (you can get the sha from [pyrcmip's PyPI](#) by clicking on 'Download files' on the left and then clicking on 'SHA256' of the `.tar.gz` file to copy it to the clipboard)
5. `git add .`
6. `git commit -m "Update to vX.Y.Z"`
7. `git push`
8. Make a PR into the [pyrcmip conda feedstock](#)
9. If the PR passes (give it at least 10 minutes to run all the CI), merge
10. Check <https://anaconda.org/conda-forge/pyrcmip> to double check that the version has increased (this can take a few minutes to update)

### 2.3.6 Why is there a Makefile in a pure Python repository?

Whilst it may not be standard practice, a `Makefile` is a simple way to automate general setup (environment setup in particular). Hence we have one here which basically acts as a notes file for how to do all those little jobs which

we often forget e.g. setting up environments, running tests (and making sure we're in the right environment), building docs, setting up auxillary bits and pieces.

## 2.3.7 Why did we choose a BSD 2-Clause License?

We want to ensure that our code can be used and shared as easily as possible. Whilst we love transparency, we didn't want to **force** all future users to also comply with a stronger license such as AGPL. Hence the choice we made.

We recommend [Morin et al. 2012](#) for more information for scientists about open-source software licenses.

## 2.4 Command-line interface

### 2.4.1 rcmip

Command-line interface for pyrcmip

```
rcmip [OPTIONS] COMMAND [ARGS]...
```

#### Options

**--log-level** <log\_level>

**Options** DEBUG|INFO|WARNING|ERROR|EXCEPTION|CRITICAL

#### upload

Validate and upload data to RCMIP's S3 bucket.

All the files for a given version have to be uploaded together.

One or more `TIMESERIES` files in which the timeseries output is stored. These should be CSV or NetCDF files conforming to the format expected by `scmdata`. Multiple timeseries inputs can be specified, but care must be taken to ensure that all of the individual timeseries have unique metadata.

`MODEL_REPORTED` is the CSV file in which the model reported metrics are stored.

`METADATA` is the CSV file in which the metadata output is stored.

```
rcmip upload [OPTIONS] TIMESERIES... MODEL_REPORTED METADATA
```

#### Options

**--token** <token>

**Required** Authentication token. Contact [zebedee.nicholls@climate-energy-college.org](mailto:zebedee.nicholls@climate-energy-college.org) for a token

**--bucket** <bucket>

**--model** <model>

**Required**

**--version** <version>

**Required** Version of the data being uploaded. Must be a valid semver version string (<https://semver.org/>). For example 2.0.0



## Arguments

### **TIMESERIES**

Required argument(s)

### **MODEL\_REPORTED**

Required argument

### **METADATA**

Required argument

## validate

Validate submission input

Three different types of input data are required for validation, namely:

One or more **TIMESERIES** files in which the timeseries output is stored. These should be CSV or NetCDF files conforming to the format expected by `scmdata`. Multiple timeseries inputs can be specified, but care must be taken to ensure that all of the individual timeseries have unique metadata.

**MODEL\_REPORTED** is the CSV file in which the model reported metrics are stored.

**METADATA** is the CSV file in which the metadata output is stored.

```
rcmip validate [OPTIONS] TIMESERIES... MODEL_REPORTED METADATA
```

## Arguments

### **TIMESERIES**

Required argument(s)

### **MODEL\_REPORTED**

Required argument

### **METADATA**

Required argument

## 2.5 Database API

Database of results handling

**class** `pyrcmip.database.Database` (*root\_dir*)

On-disk database handler for outputs from SCMs

**get\_out\_filepath** (*climate\_model, variable, region, scenario, ensemble\_member=None*)

Get filepath in which data has been saved

The filepath is the root directory joined with the other information provided. The filepath is also cleaned to remove spaces and special characters.

### Parameters

- **climate\_model** (*str*) – Climate model to retrieve data for
- **variable** (*str*) – Variable to retrieve data for
- **region** (*str*) – Region to retrieve data for

- **scenario** (*str*) – Scenario to retrieve data for
- **ensemble\_member** (*str or None*) – Ensemble member to retrieve data for

**Returns** Path in which to save the data. If `ensemble_member` is `None` then it is not included in the filename.

**Return type** *str*

**load\_data** (*variable, region, scenario*)

Load data from the database

**Parameters**

- **variable** (*str*) – Variable to load
- **region** (*str*) – Region to load
- **scenario** (*str*) – Scenario to load

**Returns** Loaded data

**Return type** *obj: scmdata.ScmRun*

**load\_model\_reported** ()

Load all model reported results

**Returns** All model reported results

**Return type** *pd.DataFrame*

**load\_summary\_tables** ()

Load all summary tables

**Returns** All summary tables

**Return type** *pd.DataFrame*

**save\_condensed\_file** (*scmrun*)

Save results which have multiple ensemble members

**Parameters** *scmrun* (*scmdata.ScmRun*) – Results to save in the database

**Raises** **AssertionError** – `ensemble_member` is not included in `scmrun`'s metadata

**save\_model\_reported** (*res, key='all'*)

Save model reported data into the database

**Parameters**

- **res** (*pd.DataFrame*) – Model reported results to save
- **key** (*str*) – Identifier to use in the filename

**Raises** **AssertionError** – The columns of `res` are not as expected (i.e. `{"value", "ensemble_member", "RCMIP name", "unit", "climate_model"}`) or more than one climate model is included in `res`.

**save\_summary\_table** (*res, file\_id*)

Save summary table

**Parameters**

- **res** (*pd.DataFrame*) – Summary table to save
- **file\_id** (*str*) – Identifier to use in the filename

Raises **AssertionError** – Columns of `res` are not as expected (i.e. not equal to `{"assessed_range_label", "assessed_range_value", "climate_model", "climate_model_value", "metric", "percentage_difference", "unit"}`)

**save\_to\_database** (*scmrun*)

Save a set of results to the database

The results are saved with one file for each `["climate_model", "variable", "region", "scenario", "ensemble_member"]` combination.

**Parameters** `scmrun` (`scmdata.ScmRun`) – Results to save

`pyrcmip.database.time_mean` (*self*, *variable=None*)

Take time mean of data

TODO: move to `scmdata` and make method of `ScmRun`.

**Parameters** `variable` (*str*) – Value of the variable column in the output. If `None`, the values are not altered from those in `self`.

**Returns** Time mean of the data

**Return type** `pd.Series`

## 2.6 Errors API

Custom errors defined within `pyrcmip`

**exception** `pyrcmip.errors.ProtocolConsistencyError`

Inconsistency between input data and the RCMIP protocol

## 2.7 IO API

Input and output handling

`pyrcmip.io.ensure_dir_exists` (*fp*)

Ensure directory exists

**Parameters** `fp` (*str*) – Filepath of which to ensure the directory exists

`pyrcmip.io.read_results_submission` (*results*)

Read results submission

**Parameters** `results` (*str or list of str*) – Files to read in. All files to be read should be formatted as csv or xlsx files following the formatting defined in the template spreadsheet.

**Returns** Results read in from the submission(s)

**Return type** `scmdata.ScmRun`

`pyrcmip.io.read_submission_model_metadata` (*fp*)

Read the model metadata component of a submission

**Parameters** `fp` (*str*) – Filepath to read

**Returns**

**Return type** `pd.DataFrame`

`pyrcmip.io.read_submission_model_reported(fp)`

Read the model reported component of a submission

**Parameters** `fp` (*str*) – Filepath to read

**Returns**

**Return type** `pd.DataFrame`

`pyrcmip.io.temporary_file_to_upload(df, max_size=1024, compress=False)`

Create a gzipped temporary serialized version of a file to upload

Attempts to keep the file in memory until it exceeds *max\_size*. The file is then stored on-disk and cleaned up at the end of the context.

The temporary location can be overridden using the *TMPDIR* environment variable as per <https://docs.python.org/3/library/tempfile.html#tempfile.gettempdir>

**Parameters**

- **df** (`scmdata.ScmRun` or `pd.DataFrame`) – Run to store
- **max\_size** (*int* or *float*) – Max size in MB before file is temporarily streamed to disk. Defaults to 1GB

**Returns** Open file object ready to be streamed

**Return type** `tempfile.SpooledTemporaryFile`

## 2.8 Metric Calculations API

Metric calculations used in RCMIP

`pyrcmip.metric_calculations.calculate_transient_climate_response(assessed_ranges, res_calc, norm_period, evaluation_period, unit)`

Calculate the transient climate response (TCR)

**Parameters**

- **assessed\_ranges** (`pyrcmip.assessed_ranges.AssessedRanges`) – Assessed ranges instance
- **res\_calc** (`scmdata.ScmRun`) – Results from which the TCR is to be derived
- **norm\_period** (*list*) – Years to use for normalising the data before calculating the TCR
- **evaluation\_period** (*list*) – Years to use when evaluating the TCR
- **unit** (*str*) – Unit in which the TCR should be returned

**Returns** TCR with other relevant model metadata

**Return type** `pd.DataFrame`

**Raises** `NotImplementedError` – The evaluation period is not the year 1920 i.e. the experiment does not match the CMIP6 specifications



- **protocol\_variables** (pd.DataFrame) – Variables and units as defined by the RCMIP protocol

**Returns** Submission with units converted to RCMIP units

**Return type** `scmdata.ScmRun`

**Raises** *ProtocolConsistencyError* – Units could not be converted to RCMIP units

`pyrcmip.validate.validate_regions` (*regions\_to\_check*, *protocol\_regions*)

Validate regions against regions in the RCMIP protocol

**Parameters**

- **regions\_to\_check** (*list-like*) – Regions to check
- **protocol\_regions** (*list-like*) – Regions in the RCMIP protocol

**Raises** *ProtocolConsistencyError* – *regions\_to\_check* contains regions not included in *protocol\_regions*

`pyrcmip.validate.validate_scenarios` (*scenarios\_to\_check*, *protocol\_scenarios*)

Validate scenarios against scenarios in the RCMIP protocol

**Parameters**

- **scenarios\_to\_check** (*list-like*) – Scenarios to check
- **protocol\_scenarios** (*list-like*) – Scenarios in the RCMIP protocol

**Raises** *ProtocolConsistencyError* – *scenarios\_to\_check* contains scenarios not included in *protocol\_scenarios*

`pyrcmip.validate.validate_submission` (*submission*, *protocol=None*)

Validate that an RCMIP submission complies with the required data format

**Parameters**

- **submission** (`scmdata.ScmRun`) – Data to validate
- **protocol** (*str*) – Data file containing the RCMIP protocol against which to validate the data. If *None*, the submission template will be loaded from `pyrcmip/data/rcmip-data-submission-template-v4-0-0.xlsx`.

**Returns** Input data, converted to match RCMIP units

**Return type** `scmdata.ScmRun`

**Raises** *ProtocolConsistencyError* – The data is not consistent with the protocol

`pyrcmip.validate.validate_submission_bundle` (*timeseries*, *model\_reported*, *metadata*, *protocol=None*)

Validate that an RCMIP submission bundle complies with the required formats

**Parameters**

- **timeseries** (`scmdata.ScmRun`) – Timeseries to validate
- **model\_reported** (pd.DataFrame) – Model reported metrics
- **metadata** (pd.DataFrame) – Model metadata
- **protocol** (*str*) – Data file containing the RCMIP protocol against which to validate the timeseries. If *None*, the submission template will be loaded from `pyrcmip/data/rcmip-data-submission-template-v4-0-0.xlsx`.

**Returns** Validated timeseries, model reported metrics and model metadata

**Return type** (`scmdata.ScmRun`, `pd.DataFrame`, `pd.DataFrame`)

**Raises**

- **`ProtocolConsistencyError`** – The submission bundle is not consistent with the RCMIP protocol
- **`ValueError`** – A value for `climate_model` is found in `timeseries` or `model_reported` but isn't found in the `climate_model` column of `metadata`.

`pyrcmip.validate.validate_submission_model_meta(inp)`

Validate a submission's metadata

**Parameters** `inp` (`pd.DataFrame`) – Metadata submission to validate

**Returns** Validated metadata submission

**Return type** `pd.DataFrame`

**Raises** **`ProtocolConsistencyError`** – The columns of `res` are not as expected (i.e. `{"climate_model", "climate_model_name", "climate_model_version", "climate_model_configuration_label", "climate_model_configuration_description", "project", "name_of_person", "literature_reference"}`).

`pyrcmip.validate.validate_submission_model_reported_metrics(inp)`

Validate a submission of model reported metrics

**Parameters** `inp` (`pd.DataFrame`) – Input to validate

**Returns** Validated input

**Return type** `pd.DataFrame`

**Raises** **`ProtocolConsistencyError`** – The columns of `res` are not as expected (i.e. `{"value", "ensemble_member", "RCMIP name", "unit", "climate_model"}`), more than one climate model is included in `res`, the `ensemble_member` column is not integers, an unrecognised metric is provided or the provided unit is not compatible with RCMIP.

`pyrcmip.validate.validate_variables(vars_to_check, protocol_variables)`

Validate variables against variables in the RCMIP protocol

**Parameters**

- **`vars_to_check`** (*list-like*) – Variables to check
- **`protocol_variables`** (*list-like*) – Variables in the RCMIP protocol

**Raises** **`ProtocolConsistencyError`** – `vars_to_check` contains variables not included in `protocol_variables`

## 2.12 Changelog

The format is based on [Keep a Changelog](#), and this project adheres to [Semantic Versioning](#).

The changes listed in this file are categorised as follows:

- Added: new features
- Changed: changes in existing functionality
- Deprecated: soon-to-be removed features

- Removed: now removed features
- Fixed: any bug fixes
- Security: in case of vulnerabilities.

## **2.12.1 master**

### **2.12.2 v0.2.1 - 2020-09-01**

#### **Added**

- (!18) Clarification that pyrcmp only supports Python 3.6+
- (!18) Add support from submission from gzipped csv
- (!16) Add the ability to specify multiple timeseries files via the CLI. Closes (#3)

### **2.12.3 v0.2.0 - 2020-08-17**

#### **Added**

- (!14) Check if the templates have changed during CI
- (!12) Add readthedocs configuration
- (!10) Documentation of submission process
- (!6) Skeleton of data processing, including illustrative model submission and processing pipeline
- (!5) Basic docs

#### **Changed**

- (!13) Fix broken documentation on readthedocs
- (!8) Upload data, metadata and model reported values together
- (!7) Require validation before uploading
- (!6) Submissions now require three parts: timeseries, model reported and metadata rather than only just one
- (!4) Require scmdata  $\geq$  0.6.1

### **2.12.4 v0.1.1 - 2020-07-09**

#### **Changed**

- Fixed readme



## 2.12.5 v0.1.0 - 2020-07-09

### Added

- CLI framework
- Basic checks



**INDEX**

- genindex
- modindex
- search



## BIBLIOGRAPHY

- [1] Z. R. J. Nicholls, M. Meinshausen, J. Lewis, R. Gieseke, D. Dommenges, K. Dorheim, C.-S. Fan, J. S. Fuglestad, T. Gasser, U. Gollüke, P. Goodwin, E. Kriegler, N. J. Leach, D. Marchegiani, Y. Quilcaille, B. H. Samset, M. Sandstad, A. N. Shiklomanov, R. B. Skeie, C. J. Smith, K. Tanaka, J. Tsutsui, and Z. Xie. Reduced complexity model intercomparison project phase 1: protocol, results and initial observations. *Geoscientific Model Development Discussions*, 2020:1–33, 2020. URL: <https://gmd.copernicus.org/preprints/gmd-2019-375/>, doi:10.5194/gmd-2019-375.



## PYTHON MODULE INDEX

### p

- `pyrcmip.database`, [13](#)
- `pyrcmip.errors`, [15](#)
- `pyrcmip.io`, [15](#)
- `pyrcmip.metric_calculations`, [16](#)
- `pyrcmip.plotting`, [17](#)
- `pyrcmip.stats`, [17](#)
- `pyrcmip.validate`, [17](#)





## Symbols

-bucket <bucket>  
     rcmip-upload command line option, 12  
 -log-level <log\_level>  
     rcmip command line option, 12  
 -model <model>  
     rcmip-upload command line option, 12  
 -token <token>  
     rcmip-upload command line option, 12  
 -version <version>  
     rcmip-upload command line option, 12

## C

calculate\_transient\_climate\_response()  
     (in module *pyrcmip.metric\_calculations*), 16  
 CLIMATE\_MODEL\_PALETTE (in module *pyrcmip.plotting*), 17  
 CMIP6\_NAME (in module *pyrcmip.plotting*), 17  
 convert\_units\_to\_rcmip\_units() (in module *pyrcmip.validate*), 17

## D

Database (class in *pyrcmip.database*), 13

## E

ensure\_dir\_exists() (in module *pyrcmip.io*), 15

## G

get\_out\_filepath() (*pyrcmip.database.Database* method), 13  
 get\_skewed\_normal() (in module *pyrcmip.stats*), 17

## L

load\_data() (*pyrcmip.database.Database* method), 14  
 load\_model\_reported() (*pyrcmip.database.Database* method), 14  
 load\_summary\_tables() (*pyrcmip.database.Database* method), 14

## M

METADATA  
     rcmip-upload command line option, 13  
     rcmip-validate command line option, 13  
 MODEL\_REPORTED  
     rcmip-upload command line option, 13  
     rcmip-validate command line option, 13

## P

ProtocolConsistencyError, 15  
*pyrcmip.database* (module), 13  
*pyrcmip.errors* (module), 15  
*pyrcmip.io* (module), 15  
*pyrcmip.metric\_calculations* (module), 16  
*pyrcmip.plotting* (module), 17  
*pyrcmip.stats* (module), 17  
*pyrcmip.validate* (module), 17

## R

rcmip command line option  
     -log-level <log\_level>, 12  
 rcmip-upload command line option  
     -bucket <bucket>, 12  
     -model <model>, 12  
     -token <token>, 12  
     -version <version>, 12  
 METADATA, 13  
 MODEL\_REPORTED, 13  
 TIMESERIES, 13  
 rcmip-validate command line option  
     METADATA, 13  
     MODEL\_REPORTED, 13  
     TIMESERIES, 13  
 read\_results\_submission() (in module *pyrcmip.io*), 15  
 read\_submission\_model\_metadata() (in module *pyrcmip.io*), 15  
 read\_submission\_model\_reported() (in module *pyrcmip.io*), 15

## S

`save_condensed_file()` (*pyrcmip.database.Database method*), 14  
`save_model_reported()` (*pyrcmip.database.Database method*), 14  
`save_summary_table()` (*pyrcmip.database.Database method*), 14  
`save_to_database()` (*pyrcmip.database.Database method*), 15  
`SCENARIO_PALETTE` (*in module pyrcmip.plotting*), 17

## T

`temporary_file_to_upload()` (*in module pyrcmip.io*), 16  
`time_mean()` (*in module pyrcmip.database*), 15  
`TIMESERIES`  
    `rcmip-upload` command line option, 13  
    `rcmip-validate` command line option, 13

## V

`validate_regions()` (*in module pyrcmip.validate*), 18  
`validate_scenarios()` (*in module pyrcmip.validate*), 18  
`validate_submission()` (*in module pyrcmip.validate*), 18  
`validate_submission_bundle()` (*in module pyrcmip.validate*), 18  
`validate_submission_model_meta()` (*in module pyrcmip.validate*), 19  
`validate_submission_model_reported_metrics()` (*in module pyrcmip.validate*), 19  
`validate_variables()` (*in module pyrcmip.validate*), 19